



WWW.FLASHLIGHT.COM

Engineering Data Sheet : 2117

Unit Information

2 D-Cell Flashlight
Model #: 2117
UPC-IC (12 Digit): 01673137403

Unit Dimensions

Length: 8.1 in. (20.6 cm)
Width: 2.3 in. (5.8 cm) at head
Height: N/A

Master Pack Dimensions

Weight: 4.9 lbs. (2.2 kg)
Cube: 0.39 ft³ (0.01 m³)
Quantity: 12

Specifications

Power Source: Alkaline or Carbon Zinc:
2xD-cell
Bulb/Lamp: PR-2
Bulb/Lamp Life: 15 Hours
Light Output: 10,000 Beam Candlepower
Weight (Without batteries): 4.5 oz (.13 kg)

Components

Lens Ring: Polypropylene (Black)
Lens: Unbreakable Tuflexx®
Reflector: ABS
Tube: Polypropylene (Safety Orange)
Contact Strip: Phosphor Bronze
Switch: Polyethylene
Bottom Cap: Polypropylene (Black)
Ring Hanger: ABS (Safety Orange)

Product Features

- For use in hazardous atmospheres
- Division 1 UL & CUL approved
- Lower cost of maintenance
- Spare bulb compartment
- Crush-resistant case
- Switch guard
- Ring Hanger
- 250,000 cycle positive locking switch
- Anti-roll tube
- Oversized, faceted reflector for more light
- Unbreakable lens



Model # 2117

Safety Approvals

UL & CUL: Class I, Division 1, Group C & D
Class I, Division 2, Group A, B, C, & D
Class II, Division 1, Group G
Class III
Operating Temp T3C
CSA: Class I, Division 1, Group C & D
Class II, Division 1, Group G
Operating Temp T3C
ASTM & MSHA Approved

Accessories Available

SP-051 6-1/2" Red Snap In Wand
SP-052 6-1/2" Yellow Snap In Wand
SP-053 6-1/2" White Snap in Wand
SP-054 Orange Slip on Wand
595 Heavy Duty Leather Belt Holder
596 Velcro Belt Holster