



## 2217 LED ATEX Specifications

### Unit Information

Model #: 2217LED ATEX / Item #16460  
UPC-IC (12 Digit): 016731164607

### Master Pack Dimensions

Weight: 9.9 lbs. (4.5 kg)  
Cube: 1.43 ft<sup>3</sup> (0.04 m<sup>3</sup>)  
Quantity: 24

### Specifications

Power Source: 2x 'D' Cell Alkaline  
Light Source: LED  
Life: 30,000 hrs  
Runtime: 200 hrs  
Light Output: 50 Lumens/ 2,450 Candelas  
Beam Distance: 99 Meters  
Weight (Without batteries): 5.0 oz (.13 kg)

### Product Features

- For use in hazardous atmospheres
- 'S' Biner included for quick attachment
- Waterproof, IP67 rating
- 'Switch Guard' Prevents accidental lighting
- Three-way switch : On-Momentary-Off
- Anti-roll tube

### Unit Dimensions

Length: 8.1 in. (20.6 cm)  
Width: 2.3 in. (5.8 cm) at head

### Safety Approvals

UL Protection Methods  
UL 913 CSA C22.2  
Intrinsically Safe  
Class I, Division 1 & 2 Groups A, B, C, D  
Class II, Division 1 & 2 Groups E, F, G  
Class III Division 1 & 2  
Operating Temp T5



IECEX & ATEX Protection Methods  
Ex ib IIC Ga, Temp Code T5; II 1GD  
ZONE I

**Approved For use with Duracell MN1300 or Energizer E95 cells only**



**WorkSafe™ Model # 2217LED ATEX**

23853	6 ½" Red Snap In Wand
23860	6 ½" Yellow Snap In Wand

