1 CHANNEL WITH ADA RAMPS

ADA Compliant ramps



CABLE PROTECTORS

The widest variety of low profile, top-loading cable protectors in the industry!

Heavy duty GUARD DOG® Low Profile Cable Protectors are the most compact, top-loading cable protectors on the market. They provide a safe and easy crossing for vehicle and pedestrian traffic and are perfect for valuable electrical and delicate multi-media electronic cables. These low profile protectors with Dog-Bone connectors are available with standard ramps or with low angle ADA Compliant ramps. Multi-channel models allow cable/hose lines to be separated in their own protective channels while the low angle ramps allow effortless crossing. Ideal for stage, studio, and broadcast applications.

LOW PROFILE 1 CHANNEL OPTIONS

- Hinged lid for easy cable placement
- Patented 5-bar tread surface
- Safety warning symbols molded into lid
- Carrying handle recessed underneath
- Heavy duty "Dog-Bone" connectors to extend to any desired length



GUARD DOG® LOW PROFILE 1 CHANNEL CABLE PROTECTORS

| MODEL | DESCRIPTION | A-LENGTH | B-WIDTH | C-HEIGHT | D-CHANNEL WIDTH | E-CHANNEL HEIGHT | WEIGHT | END VIEW |
|--|--|-------------------|----------------------|--------------------|--------------------|------------------|---------------------|----------|
| GD1X75-ST | 1 Channel Protector w Standard Ramps | 36 in. (914.4 mm) | 10.81 in. (274.6 mm) | 1.25 in. (31.8 mm) | 2.25 in. (57.2 mm) | .75 in. (19 mm) | 7.8 lbs. (3.54 kg) | |
| GD1X75-STRP | 1 Channel Standard Ramps w Rubber Pads | 36 in. (914.4 mm) | 10.81 in. (274.6 mm) | 1.25 in. (31.8 mm) | 2.25 in. (57.2 mm) | .75 in. (19 mm) | 7.8 lbs. (3.54 kg) | |
| GD1X75 | 1 Channel Protector w ADA Ramps | 36 in. (914.4 mm) | 27.25 in. (692.2 mm) | 1.25 in. (31.8 mm) | 2.25 in. (57.2 mm) | .75 in. (19 mm) | 21.1 lbs. (9.55 kg) | نا [ا |
| Protector Color: O/B = Orange Lid with Black Ramps • B/B = Black Lid with Black Ramps • O/BLU = Orange Lid with Blue Ramps (on ADA Ramp Models ONLY) | | | | | | | | В |

LOW PROFILE 2 CHANNEL OPTIONS

- Hinged lid for easy cable placement
- Patented 5-bar tread surface
- Safety warning symbols molded into lid
- Carrying handle recessed underneath
- Heavy duty "Dog-Bone" connectors to extend to any desired length

2 CHANNEL WITH STANDARD RAMPS (available with or without Anti-Slip Rubber Pads) ONLY 1.25" HIGH WITH 75" CHANNEL HEIGHT ADA Compliant ramps

GUARD DOG® LOW PROFILE 2 CHANNEL CABLE PROTECTORS

| MODEL | DESCRIPTION | A-LENGTH | B-WIDTH | C-HEIGHT | D-CHANNEL WIDTH | E-CHANNEL HEIGHT | WEIGHT | END VIEW |
|--|--|-------------------|----------------------|--------------------|------------------------|------------------|-----------------------|----------|
| GD2X75-ST | 2 Channel Protector w Standard Ramps | 36 in. (914.4 mm) | 11.94 in. (303.3 mm) | 1.25 in. (31.8 mm) | 1.5 in. (38 mm) | .75 in. (19 mm) | 9.05 lbs. (4.1 kg) | _ |
| GD2X75-STRP | 2 Channel Standard Ramps w Rubber Pads | 36 in. (914.4 mm) | 11.94 in. (303.3 mm) | 1.25 in. (31.8 mm) | 1.5 in. (38 mm) | .75 in. (19 mm) | 9.05 lbs. (4.1 kg) | |
| GD2X75 | 2 Channel Protector w ADA Ramps | 36 in. (914.4 mm) | 28.38 in. (720.9 mm) | 1.25 in. (31.8 mm) | 1.5 in. (38 mm) | .75 in. (19 mm) | 22.85 lbs. (10.36 kg) | |
| Protector Color: O/B = Orange Lid with Black Ramps • B/B = Black Lid with Black Ramps • O/BLU = Orange Lid with Blue Ramps (on ADA Ramp Models ONLY) | | | | | | | | В |

SPECIFICATION DATA

| | Polyurethane (UV stabilized) -40°F to 120°F (-40°C to 48°C) |
|--------------------|--|
| Hinge Pin Material | |
| Safety Symbols | Per ANSI. Z535.3-1991 |

LOAD CAPACITY PER TIRE/AXLE

| Channels | Max Load 70°F (2° | 1°C) | | |
|------------|-------------------|-------------|------------------|-------------|
| 1 Standard | 13,000 lbs./Tire | (5,896 kg) | 26,000 lbs./Axle | (11,792 kg) |
| 1 ADA | 23,000 lbs./Tire | (10,432 kg) | 46,000 lbs./Axle | (20,864 kg) |
| 2 Standard | 13,000 lbs./Tire | (5,896 kg) | 26,000 lbs./Axle | (11,792 kg) |
| 2 ADA | 23,000 lbs./Tire | (10.432 kg) | 46,000 lbs./Axle | (20.864 kg) |






Made in USA

FEATURES

- Available with or without ADA Compliant ramps
- 1, 2, 3, or 5 channel options
- Low profile design reduces trip hazards
- Hinged lid for easy cable placement
- Polyurethane construction
- High load-bearing capacity
- Satisfies state and federal regulatory agencies
- Modular interlocking design is easy to setup, disassemble and store

GRD-I P HND: v3 3-10





The most trusted name in cable protection!