

# SAFETY TECH PADS

**AlturnaMATS®**


From the Experts in Industrial Safety

Checkers is excited to offer our new AlturnaMATS® Safety Tech Pads!

## SAFETY TECH PADS

### FEATURES:

- Safety textured
- Safety orange TuffGrip handles
- No splinters
- No warping
- No delamination
- Lightweight & heavy duty
- Recovery memory after bending
- Engineered to bend but not break!
- Many standard sizes





Safety Texture



**THE ONLY ENGINEERED, QUANTIFIABLE AND RATED OUTRIGGER PAD AVAILABLE TODAY.**

### STANDARD PADS

MODEL	LOAD VERTICAL	LOAD 45° ANGLE	WIDTH	LENGTH	HEIGHT	WEIGHT	SQUARE INCH
PAD1515.75	45,000 lbs. (20,412 kg.)	20,000 lbs. (9,072 kg.)	15 in. (38.1 cm)	15 in. (38.1 cm)	1 in. (2.54 cm)	7.5 lbs. (3.40 kg.)	225 (1,451.70 cm <sup>2</sup> )
PAD18181	55,000 lbs. (24,948 kg.)	30,000 lbs. (13,608 kg.)	18 in. (45.72 cm)	18 in. (45.72 cm)	1 in. (2.54 cm)	11 lbs. (4.99 kg.)	324 (2,090.45 cm <sup>2</sup> )
PAD24241	60,000 lbs. (27,216 kg.)	35,000 lbs. (15,876 kg.)	24 in. (60.96 cm)	24 in. (60.96 cm)	1 in. (2.54 cm)	20 lbs. (9.07 kg.)	576 (3,761.35 cm <sup>2</sup> )
PAD24242	62,000 lbs. (28,123 kg.)	40,000 lbs. (18,144 kg.)	24 in. (60.96 cm)	24 in. (60.96 cm)	2 in. (5.08 cm)	38 lbs. (17.24 kg.)	576 (3,761.35 cm <sup>2</sup> )
PAD30301	81,000 lbs. (36,741 kg.)	41,000 lbs. (18,597.6 kg.)	30 in. (76.2 cm)	30 in. (76.2 cm)	1 in. (2.54 cm)	31 lb. (14.06 kg.)	900 (5,806.8 cm <sup>2</sup> )
PAD36361	93,000 lbs. (42,184.8 kg.)	43,000 lbs. (19,504.8 kg.)	36 in. (91.44 cm)	36 in. (91.44 cm)	1 in. (2.54 cm)	45 lb. (20.41 kg.)	1296 (8,361.79 cm <sup>2</sup> )
PAD48481	135,000 lbs. (61,236 kg.)	52,000 lbs. (23,587.2 kg.)	48 in. (121.92 cm)	48 in. (121.92 cm)	1 in. (2.54 cm)	80 lb. (36.29 kg.)	2304 (14,865.4 cm <sup>2</sup> )
PAD30302	85,000 lbs. (38,556 kg.)	43,000 lbs. (19,504.8 kg.)	30 in. (76.2 cm)	30 in. (76.2 cm)	2 in. (5.08 cm)	62 lb. (28.12 kg.)	900 (5,806.8 cm <sup>2</sup> )
PAD36362	98,000 lbs. (44,252.8 kg.)	45,000 lbs. (20,412 kg.)	36 in. (91.44 cm)	36 in. (91.44 cm)	2 in. (5.08 cm)	90 lb. (40.83 kg.)	1296 (8,361.79 cm <sup>2</sup> )
PAD48482	140,000 lbs. (63,504 kg.)	55,000 lbs. (24,948 kg.)	48 in. (121.92 cm)	48 in. (121.92 cm)	2 in. (5.08 cm)	160.0 lb. (72.58 kg.)	2304 (14,865.4 cm <sup>2</sup> )



### NOTICE:

- Foot pads must be smooth and have 80 sq. in. of surface
- Muddy or loose soil conditions may require additional shoring or stacking of pads.
- Excessive flexing and/or bending may shorten the usable life of the pad.
- Acceptable operating temperature range is -40 degrees to 180 degrees F.

\*8"x10" Outrigger Leg applied under two separate conditions: 10,000# vertically and 10,000# with a 45 degree angle.  
 \*\*TuffGrip Handle located on width side of all pads. Pads 900 sq.in. or larger have two or more handles or more handles opposite each other.  
 \*\*\*Custom size pads available. Requires a minimum order. Lead time for non-stock items is 30-45 days.\*\*\*